



**PermaWick Company**  
255 E. Brown Street, Suite 100, Birmingham, MI 48009  
Phone: 248-433-3500 • Fax: 248-594-3433  
sales@permawick.com  
www.permawick.com

**An ISO9001 Certified Company**

PD PSL 313NP

REV. # 4

REV. DATE: June 5, 2017

## **PSL313NP AND OIL**

### **POLYOLESTER BASED SYNTHETIC LUBRICANT FOR SINTERED METAL BEARINGS**

#### **DESCRIPTION**

PERMAWICK NPW is a Polyolester based synthetic oil and engineered fiber blend providing the ultimate in performance under the most grueling of conditions. Using the highest quality synthetic base stocks along with a sophisticated synergistic additive package, PSL 313 NPW is specially formulated for a long service life over a wide temperature range.

PSL313NPW is blended with a fiber specifically designed to control oil release rate in motor designs that are vulnerable to leaking.

PSL313 OIL has a proven quality record and is specifically designed to meet the lubricating needs of FHP motor sleeve bearings

#### **PRODUCT FEATURES**

- High film strength
- Low evaporation rate and oxidation resistant
- Very shear stable
- Resists rate of change of viscosity with temperature change
- Excellent anti-sludge and anti-varnish characteristics
- Useful temperature range: -40°F to 300°F (-40°C to 150°C)

<b><u>Performance Test</u></b>	<b><u>ASTM Method</u></b>	<b><u>Typicals</u></b>
Gravity, API	D1298	11.4
Specific Gravity	D1298	1.01
Color	D1500	1 – 2
Flash Point, °C	D92	240
Fire Point, °C	D92	310
Pour Point, °C	D97	-54
Viscosity, cSt. 40°C	D445	60.0
100°C		11.5
Viscosity, SUS 100°F	D445	279
210°F		65
Viscosity Index	D2270	187
Neutralization No., mg KOH/gm	D664	<2
Copper Strip Corrosion		
3 hours @ 212°F	D130	1a
Evaporation Loss, wt%		
22 hours @ 210°F	D972	0.15
<b><u>PermaWick Blend</u></b>	<b><u>ASTM Method</u></b>	<b><u>Typicals</u></b>
Fiber Content (Weight)	In-House	14% - 19%
Oil Content (Weight)	In-House	86% - 81%
Moisture Content	D95	<1.6%

**The World Leader in Fractional Horsepower Motor Lubrication**



**PermaWick Company**

**255 E. Brown Street, Suite 100, Birmingham, MI 48009**

**Phone: 248-433-3500 • Fax: 248-594-3433**

**[sales@permawick.com](mailto:sales@permawick.com)**

**[www.permawick.com](http://www.permawick.com)**

**The World Leader in Fractional Horsepower Motor Lubrication**